

PRX-20

Proximity Reader

An elegant proximity reader with a reading range of up to 10 cm.

This reader is suitable for a wide range of proximity readers based systems, such as access control and time & attendance systems.

The reader is waterproof and is therefore useful for both indoor and outdoor use.

Advantages

- Smooth and easy installation
- Quick response to card punching
- No card punching failure
- Strong remove and protection to the quick pulse interrupt / noise interrupt / static electricity & discharge electricity interrupt
- Water & dust proof
- Extended distance from controller available
- Output formats supported: 14 Char C&D, 13 Char C&D, Weigand 26

Characteristics

- Dimensions (mm): L120 X W45 X H21
- Weight: 68 g
- Power ratings: DC5 ~ 12V@80 mA
- Operating frequency: 125 KHz
- Type of cards: EM4100 (4102) or compatible
- Max transmitting distance: 300 m (in ideal condition)
- Storage temperature: -10⁰C ~ 60⁰C
- Operating temperature: -10⁰C ~ 55⁰C
- Storage humidity: 5% ~ 90%
- Operating humidity: 20% ~ 98%
- Externally activated LED indicator for Power On, OK, Error
- Externally activated buzzer indicator for OK, Error



Synel Industries Ltd.
Yokneam Industrial Park, POB 142, Yokneam 20692, Israel
Tel: +972-4-9596760 Fax: +972-4-9590729
e-mail: info@synel.co.il, Website: www.synel.com

Pictures in this brochure are for illustration purposes only.
The technical data sheet packed with the product is the only obligatory source of technical information

